

VISTIGE HYDRAULIC FLUID

ISO VG 32, 46, 68, 100, 150, 220

Vistige Hydraulic Fluid is a premium quality anti-oxidant, anti-wear, anti-rust hydraulic oil for industrial hydraulic applications blended with selected high quality base stocks and special additives to give excellent demulsibility, superior oxidation and thermal stability and excellent load-carrying capacity.

MAIN BENEFITS

- Excellent oxidation & thermal stability.
- Excellent load carrying capacity.
- Outstanding anti-wear performance.
- Superior filterability and good water separation.
- Excellent air release and antifoam properties.
- Low friction and hydraulic stability.

APPLICATION

Vistige Hydraulic Fluid can be used in all hydraulic and fluid power transmission systems suitable for a wide range of industrial applications.

SPECIFICATION

Vistige Hydraulic Fluid meets and exceeds the performance standards of Denison HFI, HF2, HFO specifications DIN 51524 PART 2, FORD M-6C32, CINCINNATI P-68, P-69, VICKERS M 29505 (Mobile Equipment), Vickers 1-2865 (Industrial Equipments) AF nor NFE 48 -603 HM, US steel 136 - 127, ASLE 64-1 to 64-4 70-1 to 70-3.

ISO Viscosity Grades	32	46	68	100	150	220
Viscosity, cSt @ 40 °C	32	45	68	102	152	222
Viscosity, cSt @ 100 °C	5.4	6.70	8.65	11.20	14.70	18.90
Viscosity Index	102	101	98	95	95	95
Pour Point	-27	-24	-21	-18	-15	-12
Flash Point COC	210	226	236	240	250	260



"Quality You Can Rely On"